

Data Sheet

Fujitsu PRIMERGY BX924 S2 Dual Socket Server Blade

Server blade with virtualization fitness at all levels, be it compute power or I/O throughput

The PRIMERGY BX Blade Servers are the ideal choice for data center solutions of today and tomorrow. Our blade servers provide maximum performance and maximum redundancy, but with only minimum space requirements, low power consumption and a reduction in the time and effort required for cabling. The PRIMERGY BX system family is designed to share components between chassis in order to react quickly and easily to changing business requirements. Storage and server blades can be added without any extra effort, as would be needed when cabling or adding management software. You can use the same applications, rely on the same server and storage components and establish connections to the same networks. The PRIMERGY BX Blade Servers are flexible and have complete control via a central administration instance that is redundant in design; they minimize administrative time and effort, freeing you of time-consuming administration tasks. Our build-to-order process ensures that only completely installed and previously tested solutions are supplied, which have been precisely adapted to individual requirements and which will grow with future business requirements.

PRIMERGY BX924 S2

The PRIMERGY BX924 S2 server blade is operated by two CPUs of the Intel® Xeon® processor 5500 and 5600 series, each with up to 6 cores. Chipset and CPU provide comprehensive, hardware based virtualization support, being supplemented by additional functions of the dual port 10 Gigabit Ethernet controller Intel® 82599, integrated on motherboard. Up to 18 DIMM modules in the system allow for a scalability that was never before possible, playing into the hands of consolidation

demands in the datacenter. A large amount of applications may be controlled by Hypervisor based solutions from VMware, Microsoft, RedHat, Suse or Citrix.

Although servers are being booted more and more via network, be it with iSCSI protocols and Ethernet, or SAN topologies and Fibre Channel, this system is enabled for local boot, too. This may optionally be realized by use of solid state drives that combine outstanding performance and high reliability.

For VMware ESXi the boot procedure may also be done using a USB connected Flash Module.

The efficient administration of the entire system via ServerView is supported by the integrated Remote Management Controller (iRMC S2); the hardware monitoring and setting options can thus be optimally visualized in order to use all options at the highest energy-efficiency levels.



Features and Benefits

Main Features	Benefits
<p>Boosting application power</p> <ul style="list-style-type: none"> Single-wide, half-high Server Blade, predestined for use as high performing application server. The Power Blade for Virtual Machines provides 18 slots for memory and abandons the use of magnetic disk drives. <p>Core technology for high performance</p> <ul style="list-style-type: none"> Next generation Intel® platform architecture realized: Intel® QuickPath for Westmere's integrated memory controllers (high-speed connections between microprocessors and external memory, and between microprocessors and the I/O hub). <p>Power consumption under control</p> <ul style="list-style-type: none"> Next generation Intel® microarchitecture with Quad- and Six-Core CPUs of the Intel® Xeon® processor 5600 series (Westmere), based on the 32-nanometer silicon technology; includes different versions from LV up to high performance models; enabled to execute four instructions per clock cycle, simultaneous multi-threading (SMT) with 2 threads per core, up to 12 MB fully inclusive, fully shared L3 cache. Extended Page Table (EPT) included. <p>Hassle-free manageability</p> <ul style="list-style-type: none"> Management with integrated Remote Management Controller (iRMC S2). <p>I/O in line with demand</p> <ul style="list-style-type: none"> IO components: dual-channel 10 Gb Ethernet on board, 2 slots for optional mezzanine cards (quad-channel 1 Gb Ethernet, dual-channel 10 Gb Ethernet, dual-channel 8 Gb Fibre Channel, dual-channel 10 Gb CNA (FCoE), dual-channel 40 Gb Infiniband) 	<ul style="list-style-type: none"> High performance with up to 12 processor cores for a wide variety of data center applications. Requirements for remote boot and maximum available memory capacity are perfectly fulfilled hereby, thus mainly virtualized environments may be served best. Easy boot of OS like a Hypervisor (e. g. VMware) via USB connected Flash Module. Best-in-class performance, bandwidth, and reliability, through integrated memory controllers and a high-speed interconnect for connecting processors and other components; enables systems to fully unleash the new levels of performance that new and more powerful next generation microarchitecture-based processor cores deliver. More performance in the same power and thermal envelope. Outstanding energy efficiency and performance on demand through dynamic management of cores, threads, cache, interfaces, and power at runtime. Improved virtualization performance due to better collaboration between guest and host OS. Server access and extensive control, even at remote locations. Routine tasks and maintenance measures in the event of server problems can be conducted remotely and efficiently, thus avoiding the need for time-consuming and cost-intensive call-outs. Use of shared or dedicated Service LAN depending on customers' demands. High IO capacity of the Blade Server system itself allows for use of a large number of diverse Server Blade internal IO components in parallel

Technical details

Mainboard

Mainboard type	D 2952
Chipset	Intel® 5500
Processor quantity and type	2 x Intel® Xeon® processor E5500 series / Intel® Xeon® processor E5600 series / Intel® Xeon® processor L5600 series / Intel® Xeon® processor X5600 series

Processor

Intel® Xeon® processor E5503 (2C/2T, 2.00 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)	
Intel® Xeon® processor E5603 (4C/4T, 1.60 GHz, SLC: -, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5606 (4C/4T, 2.13 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5607 (4C/4T, 2.26 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5620 (4C/8T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5640 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5645 (6C/12T, 2.40 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)	
Intel® Xeon® processor E5649 (6C/12T, 2.53 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)	
Intel® Xeon® processor L5630 (4C/8T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 40 W)	
Intel® Xeon® processor L5640 (6C/12T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3/4/4, 6.4 GT/s, Mem bus: 1333 MHz, 60 W)	
Intel® Xeon® processor X5647 (4C/8T, 2.93 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 130 W)	
Intel® Xeon® processor X5650 (6C/12T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5660 (6C/12T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5667 (4C/8T, 3.06 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5672 (4C/8T, 3.20 GHz, SLC: -, TLC: 12 MB, Turbo: 2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5675 (6C/12T, 3.06 GHz, SLC: -, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5677 (4C/8T, 3.46 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Intel® Xeon® processor X5687 (4C/8T, 3.60 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Intel® Xeon® processor X5690 (6C/12T, 3.46 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Processor notes	CPUs with 130W TDP not operable in combination with SSDs. Inlet temperatures higher than 30° C plus operation of CPUs with 130 W TDP or of CPUs with 95 W TDP and SSDs may lead to reduced system performance.
Memory slots	18 (3 channels per CPU with 3 slots each)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 384 GB

Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Memory Mirroring support Hot-spare memory support
Memory Modules Independent Mode	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM 2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM 16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 32 GB (1 module(s) 32 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Mirrored Mode	4 GB (2 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 8 GB (2 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 8 GB (2 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 16 GB (2 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 16 GB (2 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 32 GB (2 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Spare or Performance Mode	6 GB (3 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 12 GB (3 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 12 GB (3 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 24 GB (3 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM 24 GB (3 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM 48 GB (3 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory modules notes	Currently available 32 GB DIMMs are quad ranked and maybe installed up to 12 times; dual ranked 16 GB DIMMs may be installed 18 times.
Interfaces	
USB ports	4 x USB at the front via special cable
Graphics (15-pin)	1 x VGA at the front via special cable
Serial connection	1 x RS232 (9-pin) at the front via special cable
LAN / Ethernet (RJ-45)	2 x 10 Gbit Ethernet via Midplane to Ethernet Connection Blade
Service LAN (RJ45)	Service LAN traffic can be switched to shared onboard Gbit LAN port
I/O controller on board	
RAID controller	RAID 0/1 for internal drives
SATA Controller	ICH10R
LAN Controller	1 x Intel® 82599, 2 x 10 Gbit/s Ethernet, Intel® VT-c (includes I/OAT, VMDq, VMDc = PCI-SIG SR-IOV)
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller)
Trusted Platform Module (TPM)	Infineon / 1.2 (option)
Slots	
PCI-Express 2.0 x8	2 x BX900 Mezzanine Card
Drive bays	
Hard disk bays	2 x 2.5-inch non hot-plug SATA SSD
Operating panel	
Operating buttons	On/off switch ID button

Operating panel

Status LEDs	Power (amber / green) System status (orange) LAN connection (green) Identification (blue) CSS (yellow)
--------------------	--

BIOS

BIOS features	Local and remote update via ServerView Update Manager Online update tools for main Windows and Linux versions SMBIOS V2.6 Remote PXE boot support Remote iSCSI boot support
----------------------	---

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Microsoft® Hyper-V™ Server 2008 R2 Microsoft® Windows Server® 2008 R2 Datacenter Microsoft® Windows Server® 2008 R2 Enterprise Microsoft® Windows Server® 2008 R2 Standard Microsoft® Windows HPC Server® 2008 R2 Suite Microsoft® Windows® Small Business Server 2011 Premium Add-On Microsoft® Windows® Small Business Server Standard 2011 Microsoft® Windows® Server 2008 Datacenter Microsoft® Windows® Server 2008 Enterprise Microsoft® Windows® Server 2008 Standard Microsoft® Windows Server® 2003 Enterprise Edition Microsoft® Windows Server® 2003 Standard Edition VMware vSphere™ 5.0 Embedded VMware vSphere™ 5.0 VMware vSphere™ 4.1 VMware vSphere™ 4.1 Embedded VMware vSphere™ 4.1 Installable VMware vSphere™ 4.0 VMware vSphere™ 4.0 Embedded VMware vSphere™ 4.0 Installable Novell® SUSE Linux Enterprise Server 11 Novell® SUSE Linux Enterprise Server 10 Novell® SUSE Linux Enterprise Server 10 with XEN Red Hat® Enterprise Linux 6 Red Hat® Enterprise Linux 5 Red Hat® Enterprise Linux 5 with XEN Citrix® XenServer®
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	ASR&R Automatic Server Recovery and Restart PDA Prefailure Detection and Analysis ServerView Suite: SV Installation Manager SV Operation Manager SV RAID Manager SV Update Management SV Power Management SV Agents iRMC S2 Advanced Pack Online update packages for BIOS, firmware drivers and ServerView Agents ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version)
Option	ServerView VIOM - Virtual IO Manager ServerView Remote Management ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager
Server Management notes	Regarding Operating System dependencies for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight

Dimensions (W x D x H)	45 x 500 x 210 mm
Weight	5,75 kg
Weight notes	Actual weight may vary depending on configuration

Environmental

Temperature note	In accordance with the corresponding PRIMERGY BX900 System Unit
Operating environment	FTS 04230 Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe

Electrical values**Compliance**

Germany	GS
Europe	CE Class A *
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)

Compliance notes	In combination with corresponding PRIMERGY BX system unit There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
-------------------------	--

Compliance link	http://sp.ts.fujitsu.com/sites/certificates/
------------------------	---

Components

Storage disks	SSD SATA, 3 Gb/s, 64 GB, SLC, non hot plug, 2.5-inch, enterprise SSD SATA, 3 Gb/s, 32 GB, SLC, non hot plug, 2.5-inch, enterprise
----------------------	--

Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
------------------------	--

Mezzanine Cards

Ethernet Mezzanine Card 4 x 1 Gb Fujitsu , PCIe x4
 CNA Mezzanine Card 2 x 10 Gb Emulex (MC-CNA102E), PCIe Gen2 x8
 Ethernet Mezzanine Card 2 x 10 Gb Fujitsu , PCIe Gen2 x8
 Fibre Channel Mezzanine Card 2 x 8 Gb Emulex (MC-FC82E), PCIe x4
 InfiniBand CX2 Mezzanine Card 2 x 40 Gb Mellanox , PCIe x8
 SAS HBA Mezzanine Card x 6 Gb Fujitsu (),
 SAS RAID Mezzanine Card x 6 Gb Fujitsu (),

Warranty

Standard Warranty 3 years
Service level (depending on country)
Maintenance and Support Services - the perfect extension
Recommended Service 7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Spare Parts availability 5 years
Service Weblink <http://ts.fujitsu.com/Supportservice>

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY BX924 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX924 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/Primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2011-10-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions