

Data Sheet

FUJITSU Server PRIMEQUEST 2400E Mission Critical

No Time for Downtime

Combining the power of Intel® Xeon® E7 family processors, the standard specifications of Microsoft Windows and Linux operating systems and the wealth of market solutions with innovative fault immune system architecture for highest availability and business continuity, Fujitsu Server PRIMEQUEST systems provide a new operational efficiency for business critical computing with truly open standards. Fujitsu Server PRIMEQUEST systems hereby meet the demands of customers to expand the reach of open industry standards to include critical enterprise operation.

PRIMEQUEST 2400E Mission Critical

Fujitsu's PRIMEQUEST 2400E unite the economic and flexibility benefits of x86 industry standards with mission-critical uptime features. Customers will thus immediately benefit from a radically optimized cost effectiveness against comparable UNIX-based enterprise platforms, while preserving all the attributes so that the system always remains active. Featuring four of the Intel® Xeon® processor E7 v2 family which deliver up to 60 cores and 6TB memory, the PRIMEQUEST provides unprecedented performance and memory capacity for demanding corporate databases, mission-critical applications and in-memory solutions. Mission critical features also enable outstanding platform reliability with innovative error prevention and self-healing capabilities, such as Reserved System Board, Flexible I/O as well as physical partitioning (PPAR). Moreover, unique features, such as Dynamic Reconfiguration enable the efficient use of available resources while simplifying resource management without any need for a restart.



Features & Benefits

Main Features	Benefits
<p>Operational efficiency</p> <ul style="list-style-type: none"> ■ Combines x86 industry standard with mission-critical features ■ Eliminate costs related to the UNIX world ■ New levels of energy efficiency <p>Mission critical uptime leads to highest availability values in the x86 industry standard</p> <ul style="list-style-type: none"> ■ Different partitioning available: From software partitioning to completely isolated physical partitioning (PPAR) ■ Up to two physical partitions (PPAR): Failures of one partition do not influence other partitions ■ Active reserved system board for fast automatic recovery of services, in many cases without downtime ■ Flexible I/O ensures availability of PCIe devices ■ Almost everything is redundant ■ Online maintenance <p>Dynamic platform for demanding applications</p> <ul style="list-style-type: none"> ■ 4x Intel® Xeon® processor E7 v2 family with up to 60 cores ■ 96 DIMM slots enable a configuration of up to 6TB memory ■ 'Glue-less' design, no external QPI cables ■ Many I/O expansion options for up to 64 PCIe slots ■ Dynamic Reconfiguration enables changes in the configuration of resources and system boards without stopping the application 	<ul style="list-style-type: none"> ■ Unity of x86 efficiency and flexibility with mission-critical availability ■ Lower license fees and software maintenance costs for Oracle databases <ul style="list-style-type: none"> ■ Flexible platform to best meet individual requirements ■ Business continuity ensured even if there is a failure in one of the partitions ■ Its built-in error prevention/correction and self-healing capabilities result in outstanding platform reliability ■ All serviceable system modules can be accessed from the front or rear of the system without any cabling hassle. Moreover, Dynamic Reconfiguration enables online maintenance without the need for restarts or planned downtimes <ul style="list-style-type: none"> ■ Unprecedented performance and memory capacity for demanding corporate databases, in-memory solutions and mission-critical applications ■ I/O throughput ensured ■ Efficient usage of available resources and simplified resource management without any need for restarts

Technical details

Mainboard type	up to 2 x Systemboard		
Chipset	Intel® C104 Scalable Memory Buffer (Advanced) Intel® C602 J		
Processor quantity and type	1 - 4 x Intel® Xeon® processor E7-8800 v2 product family / Intel® Xeon® processor E7-4800 v2 product family		
Processor	Intel® Xeon® processor E7-4850v2 (12C/24T, 2.30 GHz, TLC: 24 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,333 MHz, 105 W) Intel® Xeon® processor E7-4870v2 (15C/30T, 2.30 GHz, TLC: 30 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 130 W) Intel® Xeon® processor E7-4880v2 (15C/30T, 2.50 GHz, TLC: 37.5 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 130 W) Intel® Xeon® processor E7-4890v2 (15C/30T, 2.80 GHz, TLC: 37.5 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 155 W) Intel® Xeon® processor E7-8893v2 (6C/12T, 3.4 GHz, TLC: 37.5 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 155 W)		
Memory slots	96 Max. 6 TB		
Memory slot type	DIMM (DDR3) LV		
Memory capacity (min. - max.)	16 GB - 6 TB		
Memory protection	ECC Memory Mirroring support Advanced ECC DDDC (Double Device Data Correction) SDDC		
Memory notes	Up to 96 DIMM slots per server within 2SB, each equipped with 2 Memory Mezzanine cards. 6TB will be available when 64GB LRDIMM module will shipped.		
Memory options	16 GB (2 x 8 GB) DDR3 L, registered, ECC, 1,600 MHz, PC3-12800, DIMM, 1Rx4 32 GB (2 x 16 GB) DDR3 L, registered, ECC, 1,600 MHz, PC3-12800, DIMM, 2Rx4 64 GB (2 x 32 GB) DDR3 LR, registered, ECC, 1,600 MHz, PC3-12800, DIMM, 4Rx4 128 GB (2 x 64 GB) DDR3 LR, registered, ECC, 1,333 MHz, PC3-10600, DIMM, 8Rx4		
Memory modules notes	Memory modules will be delivered in set's of 2 DIMMs per order code		
Interfaces			
Graphics (15-pin)	2 x VGA (1x per SB)		
Management LAN (RJ45)	Dedicated Service LAN port for MMB (10/100 Mbit/s)		
Onboard or integrated Controller			
RAID controller	RAID 0/1 or RAID 5/6 controller integrated in System board and/or Disk Unit (option) options are described under Components RAID controller		
LAN controller	(4 x 10/100/1000 Mbit/s Ethernet) 10GBase-SR SFP+ optical module 2 x 10 Gbit/s Ethernet		
Remote management controller	PQ2000 Management Board (MMB)		
Service Processor			
General	Management Board (MMB), located on the rear side of the system. 2nd MMB as option		
Interfaces	For Maintenance: - Local: 10/100M RJ45 for local maintenance. - Remote: 10/100M RJ45 for REMCS, AIS-Connect, ACA and ServiceLink connection (Remote monitoring service). For Management - 0/1 10M/100M/1G RJ45		
Redundancy	Up to two MMB unit can be installed in one chassis. 2nd MMB for redundancy is optional. 2nd MMB is not supported at Business model (2800B).		
I/O options			
Type	LAN ports	number of PCIe slots	Max. number per system unit
I/O Unit 10GbE full-height	2 x 10 Gbit/s Eth (RJ45)	2x PCIe Gen3 full height / 1x PCIe Gen3 low profile	4
I/O Unit 1GbE low-profile	2 x 1 Gbit/s Eth (RJ45)	4x PCIe Gen3 low profile	4
Drive bays			
Storage drive bays	2.5-inch hot-plug SAS		

Drive bays

Storage drive bay configuration	Max. 16 x 2.5-inch
---------------------------------	--------------------

General system information

Number of fans	6
Fan configuration	hot plug
Fan notes	PSU cooling fan will be used as chassis cooling facility

Operating panel

Status LEDs	System status (orange / yellow) Power (amber / green) Identification (blue)
-------------	---

RAS Features

Standard	SDDC, ECC, redundant fans and power supply
Advanced	Intra-socket memory mirroring, MCA, DDDC
Mission-Critical	Reserved SB, flex IO, Dynamic Reconfiguration, red. MMB, hot-plug PCIe

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	VMware vSphere™ 5.5
	VMware vSphere™ 5.1 Embedded
	VMware vSphere™ 5.1
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
Oracle® Linux 7	
Oracle® Linux 6	
Oracle® VM 3	

Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
-------------------------------	---

Operating system notes	Not all OSes, OS versions and server functions will be released at server release. For details refer to link below.
------------------------	---

Server Management

Standard	ServerView Suite - Maintain Remote Management (iRMC in combination with Intel® Node Manager) Update Management (BIOS, Firmware, Windows Drives and SV Agents) Performance Measurement Asset Management Online Diagnostics ServerView Suite - Integrate Integration packs e.g. for Microsoft System Center, VMware vCenter, Nagios, HP SIM and others Deployment Solutions and others ServerView Suite - Deploy SV Installation Manager ServerView Suite - Control Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) Agents and CIM Providers System Monitor RAID Manager Capacity Management Power Management Storage Support
-----------------	--

Dimensions / Weight

Rack (W x D x H)	445 x 782 x 438 mm
Height Unit Rack	10 U
19" rackmount	Yes
Weight	Up to 124 kg
Weight notes	Fully assembled Actual weight may vary depending on configuration

Environmental

Operating ambient temperature	5 - 35 °C
Operating relative humidity	20 - 80 %
Maximum altitude	3.000 m
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	60dB(80 Plus Silver), 69dB(80 Plus Platinum)
Sound power (LWAd; 1B = 10dB)	7.8B(80 Plus Silver), 8.7B(80 Plus Platinum)

Electrical values

Power supply configuration	Up to 4 hot plug power supplies. Base unit equipped with 0 power supplies, redundancy as option.
Max. input of single power supply	3200 W / 1600W (240 V / 100V)
Power supply efficiency	94 % (80 PLUS platinum) 89 % (80 PLUS silver)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	65A / 29A (100 V / 240 V)
Rated current in basic configuration	7,2A
Active power (max. configuration)	3,744 W
Heat emission	13478.4 kJ/h (12775.1 BTU/h)

Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) - planned
Europe	CE Class A *
Japan	VCCI

Compliance

Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Hard disk drives

HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise

Solid-State-Drive

SSD SAS, 12 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 1.6 TB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
PCIe-SSD AIC, 785 GB, MLC, Flash drive, 7.7 DWPD (drive writes per day)
PCIe-SSD AIC, 365 GB, MLC, Flash drive, 6 DWPD (drive writes per day)
PCIe-SSD AIC, 1.2 TB, MLC, Flash drive, 7.7 DWPD (drive writes per day)

SAS Storage Modules

SAS Ctrl., SAS/SATA 6 Gbit/s, RAID level: , based on LSI SAS2008

RAID Controller

RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, LSI MegaRAID SAS 9286CV-8e, 8 ports ext.
RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), 8 ports int.
RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)

Fibre Channel controller

Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Emulex LPe1250 MMF LC-style
Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Emulex LPe12002 MMF LC-style
Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe16000B LC-style
Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe16002B LC-style

Communication, Network

Converged Network Adapter 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Emulex)
Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 SFP+ (Fujitsu)
Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 RJ45 (Intel®)
Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
InfiniBand HCA 1 x 40 Gbit/s PCIe 3.0 x8 QSFP (Mellanox)
InfiniBand HCA 1 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox)
InfiniBand HCA 2 x 40 Gbit/s PCIe 3.0 x8 QSFP (Mellanox)
InfiniBand HCA 2 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox)

Warranty

Warranty period	3 years
Service level	Onsite Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM

Product Support Services - the perfect extension

Warranty

Service Lifecycle	5 years after end of product life
Service Weblink	www.fujitsu.com/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMEQUEST 2400E Mission Critical, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMEQUEST 2400E Mission Critical, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU Technology Solutions

Website: www.fujitsu.com
2015-04-21 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions