



Dell PowerConnect 8000 Series

The Dell™ PowerConnect™ 8000 Series is a family consisting of two switch models: PowerConnect 8024 and PowerConnect 8024F. These switches are 24-port 10 Gigabit Ethernet Layer 3 switches, with four Combo Ports for mixed cabling environments.

The PowerConnect 8000 Series are Dell's first all 10 Gigabit 1U Ethernet products. The switches are designed for utilization in a variety of environments such as 10Gb Top-of-Rack switching, 10Gb Aggregation, and Switch Core applications in small to medium data centers.

Data Center Performance

The PowerConnect 8000 Series are high density 10Gb Ethernet switches designed for data center, aggregation, and unified fabric deployments requiring high throughput and availability. These high density 24-port 10Gb switches are ready for converged Ethernet environments supporting virtualization, iSCSI storage, and 10Gb traffic aggregation. The 8000 Series also provides full routing features in a compact 1U form factor with data center friendly front-to-rear cooling.

Unified Fabric Ready

The PowerConnect 8000 Series are one of the key components in Dell Unified Fabric Data Center solutions, and support converged fabric requirements such as Priority Flow Control (802.1Qbb), iSCSI Optimization, and 10Gb wire speed performance on all ports. iSCSI traffic can also be monitored at the fabric level, allowing the administrator to track active iSCSI sessions.

10 Gb Performance and Flexibility

The PowerConnect 8000 Series bring the benefits of 10Gb Ethernet to a compact and reliable switching platform, with the quality and great service of Dell. 10Gb Ethernet provides a superior return on IT investment through:

- Investment Protection – 10Gb Ethernet is the network fabric of the future, with an ever-expanding ecosystem of solutions and the capabilities to grow
- Energy-Efficient – Replace multiple 1Gb/s components in your infrastructure to reduce power requirements and heat loads.
- High Performance – 480Gb/s of throughput for wire-speed 10Gb switching
- Migration - Support 1Gb modes on all ports for mixed environments

Energy Efficient

The PowerConnect 8000 Series is designed to be easy on budgets as well as the environment. Dell designed the PowerConnect 8000 Series for energy savings from the power cord to the ports, starting with redundant power supplies that can operate efficiently in all modes. We then added variable speed fans that adjust their speed for their environment through multiple temperature monitors. We also included power efficient 10GBASE-T ports that can reduce power draw by as much as 20%* for short cable runs, and then provided network administrators with multiple ways to manage and monitor these power savings features via command line interface (CLI), web GUI, and SNMP.

High Availability

The PowerConnect 8000 Series is designed to be highly available with dual internal hot-swap power supplies, and removable hot-swap fan modules. These switches also incorporate dual firmware images to allow for image promotions or image redundancy in a network.

Flexible Management

PowerConnect switches provide numerous management options including an industry-standard CLI, remote management using the embedded web server, and support for SNMP-based management applications including Dell OpenManage Network Manager. The web GUI for PowerConnect switches provides very robust management with comparable control to the command-line environment, allowing the administrator to choose the best method of interacting with the switch.

Dell PowerConnect 8000 Series

Layer 2/3 Ethernet switches for aggregation and data center switching in a compact 1U form factor

| Technical Specification | Dell™ PowerConnect™ 8024 and 8024F |
|---|---|
| Port Attributes | <p>8024: 24x 10GBASE-T with 4x Combo Ports of SFP+, power efficient 10GBASE-T ports that reduce power draw by as much as 20% for short cable runs, auto-negotiation for speed, duplex mode and flow control, supports converged fabric requirements such as Priority Flow Control (802.1Qbb), iSCSI Optimization, and 10Gb wire speed performance on all ports, auto-MDI/MDIX, Integrated LEDs for improved visual monitoring and analysis, cable and Transceiver Diagnostics.</p> <p>8024F: 24x SFP+ 1Gb/10Gb with 4x Combo Ports of 100M/1Gb/10GBase-T, power efficient 10GBASE-T ports that reduce power draw by as much as 20% for short cable runs, auto-negotiation for speed, duplex mode and flow control, supports converged fabric requirements such as Priority Flow Control (802.1Qbb), iSCSI Optimization, and 10Gb wire speed performance on all ports, auto-MDI/MDIX, Integrated LEDs for improved visual monitoring and analysis, cable and Transceiver Diagnostics.</p> <p>Ports support 1Gb and 10Gb transceivers for SFP/SFP+ and 100Mb, 1Gb and 10GBASE-T for RJ-45 environments.</p> |
| Performance | Total Switch Fabric Capacity up to 480 Gbps, forwarding Rate 357.14 Mpps, up to 32,000 MAC Addresses, 16 Mb Packet Buffer Memory |
| Energy Saving Features | 80% or better power supply efficiency in all operational modes, power efficient 10GBASE-T ports that can reduce power draw by as much as 20% for short cable runs, includes variable speed fans that adjust their speed for their environment through multiple temperature monitors, energy monitoring via CLI and GUI |
| Quality of Service | Layer 2 Trusted Mode (IEEE 802.1p tagging), Layer 3 Trusted Mode (DSCP), Layer 4 Trusted Mode (TCP/UDP), Advanced Mode using Layer 2/3/4 flow-based Policies, including metering/rate limiting, marking and bandwidth guarantees, 8 Priority Queues per Port, Adjustable, Weighted-Round-Robin (WRR) and Strict Queue Scheduling, Port-based QoS Services Mode, Flow-based QoS Services Mode |
| Link Aggregation | Link Aggregation with support for up to 8 member ports per aggregated link LACP support (IEEE 802.3ad) |
| VLAN | Supports up to 4000 VLANs (up to 1000 simultaneous) |
| Other Management Capabilities | |
| Environmental | 100% Lead-Free, Operating Temperature: 0° C to 40° C (0° F to 104° F), Storage Temperature: -20° C to 70° C (-4° F to 158° F), Operating Relative Humidity: 10% to 90% non-condensing, Storage Relative Humidity: 10% to 95% non-condensing |
| Power | <p>8024: Internal Power Supply Voltage AC 110/240 V +- 10% (50/60Hz); Power Consumption Max (Watts) 237.77; Power Consumption (BTU/hr) 811.39; Maximum Amperage (Inrush) 50Hz @90V 9.1A; 60Hz @90V 7.7A; 50Hz @264V 22.7A; 60Hz @264V 24.3A; Continuous Amperage (Watts) 50Hz @90V 2.63A; 60Hz @90V 2.63A; 50Hz @264V 0.98A; 60Hz @264V 1.01A; Power Supply Efficiency 80% or better in all operating modes*</p> <p>8024F: Internal Power Supply Voltage AC 110/240 V +- 10% (50/60Hz); Power Consumption Max (Watts) 160.78; Power Consumption (BTU/hr) 548.66; Maximum Wattage 160.78; Maximum Amperage (Inrush) 50Hz @90V 10.5A; 60Hz @90V 6.5A; 50Hz @264V 13.7A; 60Hz @264V 23.7A; Continuous Amperage (Watts) 50Hz @90V 1.79A; 60Hz @90V 1.8A; 50Hz @264V 0.72A; 60Hz @264V 0.75A; Power Supply Efficiency 80% or better in all operating modes*</p> |
| Standards Supported | |
| Management | <p>RFC 854, 855, 1155, 1157, 1212, 1867, 1901, 1908, 2068, 2246, 2271, 2295, 2296, 2346, 2576, 2578, 2579, 2580, 2818, 3410, 3411, 3412, 3413, 3414, 3415, 3416, 3417, 3418, 4251, 4252, 4253, 4254, 4419, 4716, 768, 783, 791, 792, 793, 826, 951, 1321, 1534, 2030, 2131, 2132, 2865, 2866, 2868, 2869, 2869bis, 3164, 3580 and 4541</p> <p>IEEE 802.1AB, 802.3, 802.3u, 802.3ab, 802.3ac, 802.3ad, 802.3ae, 802.1D, 802.1S, 802.1W, 802.1Q, 802.1v, 802.1p, 802.1X and 802.3x</p> <p>HTML 4.0 Specification - December, 1997, JavaScript™ version 1.3, SSL 3.0, SSH 1.5 & 2.0, GARP – Generic Attribute Registration Protocol, GMRP – Dynamic L2 Multicast Registration, GVRP – Dynamic VLAN Registration, XMODEM, 1. Supported via 802.1S implementation, ANSI/TIA-1057 – LLDP-MED</p> |
| Routing | RFC 826, 894, 896, 1027, 1256, 1321, 1519, 1765, 1812, 2082, 2131, 2328, 2453, 3046, 3101, 3768, 2474, 2475, 2597, 3246, 3260, 1112, 2236, 2710, 3376, 3810, 4601, 2365, 3973, 802.1p user priority (outer and/or inner VLAN tag), draft-ietf-pim-sm-bsr-05, Draft-ietf-idmr-dvmrp-v3-10 – DVMRP, draft-ietf-magma-igmp-proxy-06.txt – IGMP/MLD-based Multicast Forwarding ("IGMP/MLD Proxying"), draft-ietf-magma-igmpv3-and-routing-05.txt – IGMPv3 and Multicast Routing Protocol Interaction |
| IPv6 Routing | RFC 1981, 2373, 2460, 2461, 2462, 2464, 2711, 2740, 3315, 3484, 3493, 3513, 3542, 3587, 3736, 4213, 4291 and 4443 |
| Regulatory and Environmental Compliance | Regulatory Model: PowerConnect 8024 or 8024F, Product Safety, EMC and Environmental Datasheets, Dell Regulatory Compliance Home Page, Dell and the Environment |

*Based on Power Supply Efficiency Tests conducted by Dell, 2008.

© 2010 Dell Inc. All rights reserved. Microsoft, Windows and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Simplify your network at Dell.com/networking

