

### Overview

## Models

HP MSR20-20 Router	JF283A
HP MSR20-21 Router	JD663B
HP MSR20-40 Router	JF228A

## Key features

- Convergence of routing, switching, voice, security
- Embedded encryption, firewall, security features
- Modular design supports full portfolio modules
- Unified Management Platform
- Standards-based design provides interoperability

## Product overview

The HP MSR20 router series is a component of the FlexBranch module of the FlexNetwork Architecture. It features a modular design that delivers unmatched flexibility for small branch offices and small to medium-sized businesses while reducing complexity, simplifying management, and increasing control. The MSR20 routers provide a full-featured, resilient routing platform, including IPv6 and MPLS, up to 180 Kpps forwarding capacity, and 100 Mbps encryption. They offer lasting investment protection, and help reduce capital and operating expenses. These routers provide an agile, flexible network infrastructure that offers the ability to quickly adapt to changing business requirements while delivering integrated, concurrent services on a single, easy-to-manage platform.

## Features and benefits

### Quality of Service (QoS)

- **Traffic policing:** supports Committed Access Rate (CAR) and line rate
- **Congestion management:** supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance:** Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Other QoS technologies:** support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

### Management

- **Industry-standard CLI with a hierarchical structure:** reduces training time and expenses, and increases productivity in multivendor installations
- **Management security:** multiple privilege levels with password protection restrict access to critical configuration commands; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3:** provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)
- **Debug and sampler utility:** supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP):** synchronizes timekeeping among distributed time servers and clients; keeps consistent timekeeping among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center:** provides a central information center for system and network information; aggregates all logs, traps, and



## Overview

debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules

- **Management interface control:** provides management access through modem port and terminal interface; provides access through terminal interface, telnet, or SSH
- **Network Quality Analyzer (NQA):** analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

## Connectivity

- **3G access support:** allows use of SIC 3G module for high reliability; supports popular USB 3G modem
- **High-density port connectivity:** provides up to 4 interface module slots and up to 18 Fast Ethernet ports
- **Multiple WAN interfaces:** provide a traditional link with Serial, E1/T1, ADSL, and ISDN/AM backup; provide high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet and LAN 4-and 9-port Fast Ethernet; provide mobility access with 802.11g/n Wi-Fi and 3G
- **Packet storm protection:** protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback:** supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **Flexible port selection:** provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDI-X

## Performance

- **Powerful encryption capacity:** includes embedded hardware encryption accelerator to improve encryption performance
- **Flexible chassis selection:** offers a choice of three routers, meeting different requirements on enterprise branches
- **Excellent forwarding performance:** provides forwarding performance up to 180 Kpps; meets current and future bandwidth-intensive application demands of enterprise businesses

## Resiliency and high availability

- **Backup Centre:** acts as a part of the management and backup function to provide backup for device interfaces; delivers reliability by switching traffic over to a backup interface when the primary one fails
- **Virtual Router Redundancy Protocol (VRRP):** allows groups of two routers to dynamically back each other up to create highly available routed environments; VRRP load balancing supported

## Layer 2 switching

- **Spanning Tree:** fully supports standard IEEE 802.1D Spanning Tree Protocol, IEEE 802.1w Rapid Spanning Tree Protocol for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring:** duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **VLANs:** support up to 4,094 ports or IEEE 802.1Q-based VLANs
- **sFlow:** allows traffic sampling

## Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper:** redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and



## Overview

server; DHCP Relay enables DHCP operation across subnets

## Layer 3 routing

- **Static IPv4 routing:** provides simple, manually configured IPv4 routing
- **Routing Information Protocol:** uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **OSPF:** Interior Gateway Protocol (IGP) using link-state protocol for faster convergence; supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4):** Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS):** Interior Gateway Protocol (IGP) using path vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing:** provides simple, manually configured IPv6 routing
- **Dual IP stack:** maintains separate stacks for IPv4 and IPv6 to ease transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng):** extends RIPv2 to support IPv6 addressing
- **OSPFv3:** provides OSPF support for IPv6
- **BGP+:** extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6:** extends IS-IS to support IPv6 addressing
- **IPv6 tunneling:** is an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Multiprotocol Label Switching (MPLS):** uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- **Multiprotocol Label Switching (MPLS) Layer 3 VPN:** allows Layer 3 VPNs across a provider network; uses Multiprotocol BGP (MP-BGP) to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility; supports IPv6 MPLS VPN
- **Multiprotocol Label Switching (MPLS) Layer 2 VPN:** establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies
- **Policy routing:** allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

## Security

- **Access control list (ACL):** supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent illegal users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **TACACS+:** is an authentication tool using TCP with encryption of the full authentication request that provides additional security
- **Unicast Reverse Path Forwarding (URPF):** allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks
- **Network login:** authentication of multiple users per port
- **RADIUS:** eases security access administration by using a user/password authentication server
- **Network address translation (NAT):** supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT to support multiple connections; supports blacklist in NAT/NAPT, a limit on the number of connections, session logs, and multi-



## Overview

instances

- **Secure Shell (SSHv2):** uses external servers to securely login into a remote device; with authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers
- **IPSec VPN:** supports Encryption Algorithm (DES/3DES, AES 128/192/256), Authentication Algorithm (HMAC-MD5, HMAC-SHA-1), and IPSec for IPv6

## Convergence

- **Internet Group Management Protocol (IGMP):** is used by IP hosts to establish and maintain multicast groups; supports v1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM):** is used for IPv4 and IPv6 multicast applications; supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP):** is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

## Integration

- **Embedded NetStream:** local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- **Embedded VPN firewall:** provides enhanced stateful packet inspection and filtering; delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

## Additional information

- **OPEX savings:** a common operating system simplifies and streamlines deployment, management, and training, thereby cutting costs, as well as reducing the chance for human error associated with having to manage multiple operating systems across different platforms and network layers
- **High reliability:** provides a state-of-the-art unified code base
- **Faster time to market:** engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability
- **Green initiative support:** provides support for RoHS and WEEE regulations

## Product architecture

- **Ideal multiservice platform:** provides data, voice SIP and H.323, LAN switching, wireless, 3G, firewall, and IPSec/SSL VPN all in one box
- **Embedded service modules for security and voice:** embedded Voice Co-Processing Modules (VCPMs) and Voice Processing Modules (VPMs) accommodate digital signal processor (DSP) modules for packet voice processing; embedded hardware encryption modules, Standard Network Data Encryption (SNDE) cards, and Advanced Network Data Encryption (ANDE) cards do not occupy I/O slots
- **USB interface:** uses USB memory disk to download and upload configuration files; supports external USB 3G modem for 3G WAN uplink
- **SIP trunk:** the SIP trunk link can carry multiple concurrent calls; the carrier authenticates only the link, rather than carrying each SIP call on the link

## Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to: [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty) for details on the support provided and the period during which support is available



## Overview

- **Software releases:** refer to: [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty) for details on the software releases provided and the period during which software releases are available for your product(s)



## Technical Specifications

### HP MSR20-20 Router (JF283A)

<b>Ports</b>	2 SIC slots 2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.3(d) x 14.17(w) x 1.74(h) in. (28.71 x 36 x 4.42 cm) (1U height) <b>Weight</b> 7.5 lb. (3.4 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> 180 Kpps (64-byte packets) <b>Routing table size</b> 10000 entries
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 5% to 90%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 184 BTU/hr (194.12 kJ/hr) <b>Voltage</b> 100-120/200-240 VAC <b>Maximum power rating</b> 54 W <b>Frequency</b> 50/60 Hz <b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
<b>Emissions</b>	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001
<b>Telecom</b>	FCC part 68
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)



## Technical Specifications

- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 24x7 software phone support, software updates (HR557E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

### HP MSR20-21 Router (JD663B)

<b>Ports</b>	2 SIC slots
	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	8 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.3(d) x 14.17(w) x 1.74(h) in. (28.7 x 36 x 4.42 cm) (1U height)
	<b>Weight</b> 7.5 lb. (3.4 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> 180 Kpps (64-byte packets)
	<b>Routing table size</b> 10000 entries
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b> 5% to 90%, noncondensing
	<b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 184 BTU/hr (194.12 kJ/hr)
	<b>Voltage</b> 100-120/200-240 VAC
	<b>Maximum power rating</b> 54 W
	<b>Frequency</b> 50/60 Hz



## Technical Specifications

	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
<b>Emissions</b>	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001	
<b>Telecom</b>	FCC part 68	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.	
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)	
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

---

### HP MSR20-40 Router (JF228A)

<b>Ports</b>	4 SIC slots 2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.3(d) x 14.17(w) x 1.74(h) in. (28.71 x 36 x 4.42 cm) (1U height) <b>Weight</b> 11.9 lb. (5.4 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 400 MHz, 256 MB compact flash, 256 MB SDRAM
<b>Mounting</b>	Mounts in an EIA standard 19-in. rack





## Technical Specifications

Performance	Throughput	180 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	341 BTU/hr (359.76 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	100 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
Emissions	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union.	
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E)	



## Technical Specifications

- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 24x7 software phone support, software updates (HR557E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Standards and protocols (applies to all products in series)

#### BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

#### Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

#### General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 855 Telnet Option Specification
- RFC 856 TELNET
- RFC 858 Telnet Suppress Go Ahead Option
- RFC 894 IP over Ethernet
- RFC 925 Multi-LAN Address Resolution
- RFC 950 Internet Standard Subnetting Procedure

- RFC 3032 MPLS Label Stack Encoding
- RFC 3036 LDP Specification
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3246 Expedited Forwarding PHB
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
- RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
- RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information



## Technical Specifications

RFC 959 File Transfer Protocol (FTP)	Base (MIB)
RFC 1006 ISO transport services on top of the TCP: Version 3	RFC 3847 Restart signaling for IS-IS
RFC 1027 Proxy ARP	<b>IP multicast</b>
RFC 1034 Domain Concepts and Facilities	RFC 1112 IGMP
RFC 1035 Domain Implementation and Specification	RFC 2236 IGMPv2
RFC 1042 IP Datagrams	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1058 RIPv1	RFC 2362 PIM Sparse Mode
RFC 1071 Computing the Internet Checksum	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1091 Telnet Terminal-Type Option	RFC 3376 IGMPv3
RFC 1122 Host Requirements	<b>IPv6</b>
RFC 1141 Incremental updating of the Internet checksum	RFC 1981 IPv6 Path MTU Discovery
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	RFC 2080 RIPng for IPv6
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 2292 Advanced Sockets API for IPv6
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2373 IPv6 Addressing Architecture
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2460 IPv6 Specification
RFC 1293 Inverse Address Resolution Protocol	RFC 2461 IPv6 Neighbor Discovery
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1333 PPP Link Quality Monitoring	RFC 2472 IP Version 6 over PPP
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1349 Type of Service	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1350 TFTP Protocol (revision 2)	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2740 OSPFv3 for IPv6
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 3513 IPv6 Addressing Architecture
RFC 1519 CIDR	RFC 3596 DNS Extension for IPv6
RFC 1534 DHCP/BOOTP Interoperation	<b>MIBs</b>
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 1213 MIB II
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	RFC 1229 Interface MIB Extensions
RFC 1577 Classical IP and ARP over ATM	RFC 1286 Bridge MIB
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 1493 Bridge MIB
RFC 1624 Incremental Internet Checksum	RFC 1573 SNMP MIB II
RFC 1631 NAT	RFC 1724 RIPv2 MIB
RFC 1638 PPP Bridging Control Protocol (BCP)	RFC 1757 Remote Network Monitoring MIB



## Technical Specifications

- RFC 1661 The Point-to-Point Protocol (PPP)
  - RFC 1662 PPP in HDLC-like Framing
  - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
  - RFC 1701 Generic Routing Encapsulation
  - RFC 1702 Generic Routing Encapsulation over IPv4 networks
  - RFC 1721 RIP-2 Analysis
  - RFC 1722 RIP-2 Applicability
  - RFC 1723 RIP v2
  - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
  - RFC 1812 IPv4 Routing
  - RFC 1829 The ESP DES-CBC Transform
  - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
  - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
  - RFC 1973 PPP in Frame Relay
  - RFC 1974 PPP Stac LZS Compression Protocol
  - RFC 1990 The PPP Multilink Protocol (MP)
  - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
  - RFC 2091 Trigger RIP
  - RFC 2131 DHCP
  - RFC 2132 DHCP Options and BOOTP Vendor Extensions
  - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
  - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
  - RFC 2280 Routing Policy Specification Language (RPSL)
  - RFC 2284 EAP over LAN
  - RFC 2338 VRRP
  - RFC 2364 PPP Over AAL5
  - RFC 2374 An Aggregatable Global Unicast Address Format
  - RFC 2451 The ESP CBC-Mode Cipher Algorithms
  - RFC 2453 RIPv2
  - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
  - RFC 2511 Internet X.509 Certificate Request Message Format
  - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
  - RFC 2644 Directed Broadcast Control
  - RFC 2661 L2TP
  - RFC 2663 NAT Terminology and Considerations
  - RFC 2466 ICMPv6 MIB
  - RFC 2618 RADIUS Client MIB
  - RFC 2620 RADIUS Accounting MIB
  - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
  - RFC 2737 Entity MIB (Version 2)
  - RFC 2863 The Interfaces Group MIB
  - RFC 2933 IGMP MIB
  - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
  - RFC 1155 Structure of Management Information
  - RFC 1157 SNMPv1
  - RFC 1905 SNMPv2 Protocol Operations
  - RFC 2272 SNMPv3 Management Protocol
  - RFC 2273 SNMPv3 Applications
  - RFC 2274 USM for SNMPv3
  - RFC 2275 VACM for SNMPv3
  - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
  - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
  - RFC 1246 Experience with OSPF
  - RFC 1587 OSPF NSSA
  - RFC 1765 OSPF Database Overflow
  - RFC 1850 OSPFv2 Management Information Base (MIB), traps
  - RFC 2328 OSPFv2
  - RFC 2370 OSPF Opaque LSA Option
  - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
  - RFC 2474 DS Field in the IPv4 and IPv6 Headers
  - RFC 2475 DiffServ Architecture
  - RFC 2597 DiffServ Assured Forwarding (AF)
  - RFC 2598 DiffServ Expedited Forwarding (EF)
  - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
  - RFC 1321 The MD5 Message-Digest Algorithm
  - RFC 2082 RIP-2 MD5 Authentication
  - RFC 2104 Keyed-Hashing for Message Authentication
  - RFC 2138 RADIUS Authentication
  - RFC 2209 RSVP-Message Processing
  - RFC 2246 Transport Layer Security (TLS)
  - RFC 2716 PPP EAP TLS Authentication Protocol



## Technical Specifications

RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5  
RFC 2694 DNS extensions to Network Address Translators (DNS\_ALG)  
RFC 2702 Requirements for Traffic Engineering Over MPLS  
RFC 2747 RSVP Cryptographic Authentication  
RFC 2763 Dynamic Name-to-System ID mapping support  
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)  
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)  
RFC 2784 Generic Routing Encapsulation (GRE)  
RFC 2787 Definitions of Managed Objects for VRRP  
RFC 2961 RSVP Refresh Overhead Reduction Extensions  
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS  
RFC 2973 IS-IS Mesh Groups  
RFC 2993 Architectural Implications of NAT  
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)  
RFC 3027 Protocol Complications with the IP Network Address Translator  
RFC 3031 Multiprotocol Label Switching Architecture

RFC 2865 RADIUS Authentication  
RFC 2866 RADIUS Accounting  
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

### VPN

RFC 2403 - HMAC-MD5-96  
RFC 2404 - HMAC-SHA1-96  
RFC 2405 - DES-CBC Cipher algorithm  
RFC 2547 BGP/MPLS VPNs  
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP  
RFC 2842 Capabilities Advertisement with BGP-4  
RFC 2858 Multiprotocol Extensions for BGP-4  
RFC 2918 Route Refresh Capability for BGP-4  
RFC 3107 Carrying Label Information in BGP-4

### IPsec

RFC 1828 IP Authentication using Keyed MD5  
RFC 2401 IP Security Architecture  
RFC 2402 IP Authentication Header  
RFC 2406 IP Encapsulating Security Payload  
RFC 2407 - Domain of interpretation  
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec  
RFC 2411 IP Security Document Roadmap  
RFC 2412 - OAKLEY  
RFC 2865 - Remote Authentication Dial In User Service (RADIUS)



## Accessories

### HP MSR20 Series accessories

#### Transceivers

HP X110 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X124 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B

#### Cables

HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 E1 BNC 75 ohm 3m Router Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Router Cable	JD518A
HP X260 T1VI DB15M RJ45 3m Router Cable	JF843A
HP X260 T1 Voice Router Cable	JD535A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X260 mini D-28 to 4-RJ45 0.3m Router Cable	JG263A

#### Router Modules

HP MSR Encryption Accelerator Advanced Module	JD608A
HP MSR Standard Encryption Accelerator Module	JD609A
HP MSR 4-port 10/100Base-T Switch SIC Module	JD573B
HP MSR 1-port 10/100Base-T SIC Module	JD545B
HP MSR 1-port 100Base-X SIC Module	JF280A
HP MSR 1-port GbE Combo SIC Module	JD572A
HP MSR 2-port FXO SIC Module	JD558A



### Accessories

HP MSR 1-port FXO SIC Module	JD559A
HP MSR 2-port FXS SIC Module	JD560A
HP MSR 1-port FXS SIC Module	JD561A
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 2-port FXS/1-port FXO SIC Module	JD632A
HP MSR 2-port ISDN-S/T Voice SIC Module	JF821A
HP MSR 1-port E1/Fractional E1 (75ohm) SIC Module	JD634B
HP MSR 2-port E1/Fractional E1 (75ohm) SIC Module	JF842A
HP MSR 1-port T1/Fractional T1 SIC Module	JD538A
HP MSR 1-port Enhanced Sync/Async Serial SIC Module	JD557A
HP 1-port Analog Modem SIC MSR Module	JD536A
HP MSR 1-port ADSL over POTS SIC Module	JD537A
HP MSR 1-port ADSL over ISDN SIC Module	JG056B
HP MSR 1-port 8-wire G.SHDSL (RJ45) DSIC Module	JG191A
HP MSR 1-port ISDN-S/T SIC Module	JD571A
HP MSR 8-port Async Serial SIC Module	JF281A
HP MSR 16-port Async Serial SIC Module	JG186A
HP MSR 802.11b/g/n Wireless Access Point SIC Module	JF819A
HP MSR 802.11b/g/n Wireless Access Point SIC Module (NA)	JG211A
HP 3G Wireless GSM/WCDMA WAN SIC Module	JF820A
<b>HP MSR20-40 Router (JF228A)</b>	
HP MSR 32-Channel Voice Processing Module	JD598A
HP MSR 24-Channel Voice Processing Module	JD599A
HP MSR 16-Channel Voice Processing Module	JD600A
HP MSR 8-Channel Voice Processing Module	JD601A
HP MSR Voice Co-processing Module	JD610A
HP MSR 9-port 10/100Base-T Switch DSIC Module	JD574B





## Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<p><b>HP X120 1G SFP LC SX Transceiver (JD118B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.</p>	<b>Ports</b>	1 LC 1000BASE-SX port	
	<b>Connectivity</b>	<b>Connector type</b> LC	
	<b>Physical characteristics</b>	<b>Wavelength</b>	850 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Maximum distance:	<ul style="list-style-type: none"> <li>• FDDI Grade distance = 220m</li> <li>• OM1 = 275m</li> <li>• OM2 = 500m</li> <li>• OM3 = Not Specified by standard</li> </ul>
		Cable length	up to 550m
		Fiber type	Multi Mode
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<p><b>HP X120 1G SFP LC LX Transceiver (JD119B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF</p>	<b>Ports</b>	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
	<b>Connectivity</b>	<b>Connector type</b> LC	
	<b>Physical characteristics</b>	<b>Wavelength</b>	1300 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Cable type:	Either single mode or multimode;
		Maximum distance:	<ul style="list-style-type: none"> <li>• 550m for Multimode</li> <li>• 10km for Singlemode</li> </ul>
		Fiber type	Both





## Accessory Product Details

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X125 1G SFP LC LH40 Ports  
1310nm Transceiver  
(JD061A)**

A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.

**Connectivity**

1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)

Connector type LC

Wavelength 1310 nm

**Physical characteristics**

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

**Electrical characteristics**

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

**Cabling**

Cable type:  
Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 40km distance

Fiber type Single Mode

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X120 1G SFP LC LH40 Ports  
1550nm Transceiver  
(JD062A)**

A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.

**Connectivity**

1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)

Connector type LC

Wavelength 1550 nm

**Physical characteristics**

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

**Electrical characteristics**

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

**Cabling**

Cable type:  
Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 40km distance

Fiber type Single Mode

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



## Accessory Product Details

<b>HP X125 1G SFP LC LH70 Transceiver (JD063B)</b>	<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	<b>Connectivity</b>	<b>Connector type</b>	LC
A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.	<b>Physical characteristics</b>	<b>Wavelength</b>	1550 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
		<b>Power consumption typical</b>	0.8 W
	<b>Cabling</b>	<b>Power consumption maximum</b>	1.0 W
		<b>Cable type:</b>	Single-mode fiber optic, complying with ITU-T G.652;
<b>Services</b>	<b>Maximum distance:</b>	• 70km	
	<b>Fiber type</b>	Single Mode	
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

---

<b>HP MSR 8-port Async Serial SIC Module (JF281A)</b>	<b>Connectivity</b>	<b>Bit rate</b>	115.2Kbps
		<b>Interface</b>	RS232
	<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

---

To learn more, visit: [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2010-2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

