





HP ProLiant ML370 G6 Server

HP ProLignt DL370 G6 and HP ProLignt ML370 G6 Servers

Data sheet

Enhance data centre efficiency and get better return for your budget with the HP ProLiant DL370 G6 (4U optimised rack) and the HP ProLiant ML370 G6 (4U expandable tower) Servers.

Data centres have grown in size and complexity, and are characterised more by diversity than standardisation. This means that your IT administrators have more on their hands than ever before. As they struggle to enhance data centre efficiency, they also need to rein in rising power costs.

The HP ProLiant DL370 G6 and the HP ProLiant ML370 G6 Servers help strike that balance. HP Insight Control suite with the new Dynamic Power Capping technology can triple¹ the capacity of the data centre and tailor the power supply to the desired configuration. Talking about efficiency, both the DL370 G6 and the ML370 G6 offer the broadest range of Intel's latest processors – Intel® Xeon® 5600 and 5500 series processors. Additionally, the HP ProLiant Onboard Administrator powered by the Integrated Lights-Out 2, offers features like simplified server setup, health monitoring, power optimisation, thermal control and remote management.

Key features and benefits

The DL370 (4U rack-optimised chassis) and the ML370 (expandable tower chassis) servers deliver industry-leading management tools, performance, expandability, flexibility and the latest energy-efficient technologies. These servers have

been optimised for virtualisation and consolidation environments, and are well-suited for deployment in growing businesses, remote office sites or data centres and have also been designed to bring you the utmost confidence to run your business.

Enhanced performance

The DL370 G6 and the ML370 G6 promise to deliver enterprise-class performance. Both of these servers come equipped with Intel Xeon 5600 and 5500 series processors. The DDR3 memory technology offers twice² the bandwidth, double the capacity and 25% less power and since both of these servers support 18 DIMM slots, customers can achieve up to 192 GB of DDR3 registered memory. Both the DL370 G6 and the ML370 G6 include the new generation of HP Smart Array Modular Controllers delivering 200% greater performance³ and enhanced backward compatibility.

http://www.jedec.org/standards-documents/docs/jesd-79-3d



¹ HP Performance Engineering Team, 2008 Benchmark. For more details, visit: www.hp.com/go/reclaimcapacity

² When moving from DDR2 to DDR3, memory bandwidth doubled from 667 to 1333 MHz. JEDEC is the governing body of memory standards. For more information, visit:

³ The bandwidth of the controller has doubled from 3 Gb/s SAS to 6 Gb/s SAS, equalling 2x the bandwidth or 200% faster. Workloads, applications and environments may affect actual performance. For more information, visit: www.scsita.org/aboutscsi/sas/definition.html

Configure an optimised server – with the confidence of knowing it is right. Use ProLiant Solution Blocks and HP configuration tools co-designed and validated with leading software vendors and their energy-efficient leadership.

Improved power management

Struggling to get your soaring power bills under control? Not only do the right-sized ProLiant power supplies help reclaim lost data centre power, but the Intelligent Power and Cooling Savers can tell when power is being wasted. Correspondingly, you get to improve your IT architecture's capacity up to 3x with Dynamic Power Capping, which is available as part of the Insight Control suite. In addition, the Intel 45 nanometer technology and dynamic resource scaling further enable more efficient power management.

Supporting the high-efficiency power supplies, both the DL370 G6 and the ML370 G6 servers put a check on your undesirable power consumption. Improved power efficiency enabled by HP ProLiant Common Slot Power Supplies (460 W and 750 W)⁴ and HP ProLiant Common Slot Power Supplies (1200 W)⁵ has earned the servers various energy saving certifications.

Deploy easily, manage seamlessly

The ProLiant family of deployment tools, such as SmartStart, Preboot Execution Environment (PXE), Array Configuration Utility (ACU) and ROM-Based Setup Utility (RBSU), enables a hassle-free setup. The HP ProLiant Onboard Administrator and HP Systems Insight Manager give you the flexibility to manage and monitor all your DL370 G6 and ML370 G6 servers seamlessly, and make them an ideal fit for remote deployments.

Enterprise-class redundancy features

Business continuity is a must for businesses, both big and small. Intolerant to downtime as your business is, you can count on the DL370 G6 and the ML370 G6 servers to deliver 24x7 accessibility and proven data integrity. There are three hot-plug fans, which is a standard option with every system. For full redundancy features, you can purchase the DL370 G6 and ML370 G6 redundant fan kit. Combined with this is the availability of two processors and support for redundant power supplies delivering high-availability and high-performance system processing.

Increased flexibility

Both of these servers support PCI Express Gen2 slots (nine available), which, coupled with the 8-bay drive cage, provide room for expansion. Another outstanding feature is the flexibility of the tower models to convert to rack configurations, providing your infrastructure with additional deployment flexibility.

Enhance system performance and ease of serviceability

With their inherent features that enhance business outcomes and facilitate ease of serviceability, the ProLiant DL370 G6 and the ML370 G6 Servers have achieved numerous No.1 benchmarks – VMmark, TPC-C, SPECweb2005 and SPECweb2009. Feature enhancements like nine available PCI Express Gen2 slots, 18 DIMM memory slots supporting Advanced ECC, mirroring mode and lock-step mode give these two servers a visible competitive advantage. For tool-free internal serviceability, snap-on quick deploy slide rails are included with rack models and tower-to-rack conversion kits. They enable rapid installation and save valuable time.

Watch the HP product marketing manager demo the HP ProLiant ML/DL370 G6 Server



Ideal environments

A variety of environments from corporate workgroups to critical remote sites

With their large internal storage capacity – accommodating everything from web applications to databases – 24x7 accessibility and ease of serviceability, the DL370 G6 and the ML370 G6 servers are ideal choices for virtualisation and consolidation environments spanning across corporate workgroups to critical remote sites.

Click here to view the demo and get an overview of the HP ProLiant ML/DL370 G6 Server



- ⁴ Meet Climate Savers Computing Initiative GOLD, ECOS Consulting 80 PLUS GOLD and the standard specifications for Energy Star for Servers Power Supply requirements
- Meet Climate Savers Computing Initiative BRONZE, ECOS Consulting 80 PLUS BRONZE Power Supply requirements

Technical specificationsHP ProLiant DL370 G6 and HP ProLiant ML370 G6 Servers Processor and memory

Processor type	Intel Xeon 5600 and 5500 series processors					
Available processors	Intel naming	Speed (GHz)	L3 cache (MB)	Wattage (W)	Turbo	DDR3 memory (MHz)
	Six-core processors					
	X5690	3.46	12	130 W	1/1/1/1/2/2	1333
	X5680	3.33	12	130 W	1/1/1/1/2/2	1333
	X5675	3.06	12	95 W	2/2/2/2/3/3	1333
	X5670	2.93	12	95 W 95 W	2/2/2/2/3/3	1333
	X5660 X5650	2.80 2.66	12 12	95 W	2/2/2/2/3/3 2/2/2/2/3/3	1333 1333
	E5649	2.53	12	80 W	1/1/1/1/2/2	1333
	E5645 2.40 12 80 W 1/1/1/1/2/2 1333					
	Quad-core processors					
	X5687	3.60	12	130 W	1/1/2/2	1333
	X5677	3.46	12	130 W	1/1/2/2	1333
	X5672 X5667	3.20	12 12	95 W 95 W	2/2/3/3	1333 1333
	E5640	3.06 2.66	12	95 W 80 W	2/2/3/3 1/1/2/2	1066
	E5630	2.53	12	80 W	1/1/2/2	1066
	E5620	2.40	12	80 W	1/1/2/2	1066
	W5580	3.20	8	130 W	1/1/1/2	1333
	X5570	2.93	8	95 W	2/2/3/3	1333
	X5560	2.80	8	95 W	2/2/3/3	1333
	X5550	2.66	8	95 W	2/2/3/3	1333
	E5540	2.53	8	80 W	1/1/2/2	1066
	E5530	2.40	8	80 W	1/1/2/2	1066
	E5520	2.26	8	80 W	1/1/2/2	1066
	E5607	2.26	8	80 W	N/A	1066
	E5606	2.13	8	80 W	N/A	1066
	E5506	2.13	4	80 W	N/A	800
	E5504	2.00	4	80 W	N/A	800
	E5603 Quad-core processo	1.60 ors (low voltage)	4	80 W	N/A	1066
	L5630	2.13	12	40 W	1/1/2/2	1066
	L5520	2.26	8	60 W	1/1/2/2	1066
	Dual-core processor E5502		4	80 W	N/A	800
Processor core	6-, 4- and 2-core pro		4	00 VV	IN/A	800
	<u> </u>		, l l l			
Processor cache	12, 8 and 4 MB Level 3 cache depending on processor (see above)					
Maximum processor speed	3.46 GHz					
Multiprocessor	Up to 2					
Memory type	PC3-10600R Registered (DDR3) Memory or PC3-10600E Unbuffered (DDR3) Memory					
Standard memory	Standard (Performance Models) – 12 GB (6 x 2 GB) RDIMM Standard (Base Models) – 6 GB (3 x 2 GB) RDIMM Standard (Entry Model) – 4 GB (2 x 2 GB) RDIMM Note: Depending on the memory configuration and processor model, the memory speed may run at 1333 MHz, 1066 MHz or 800 MHz. Please see the Online Memory Configuration Tool.					
	Standard (Base Mod Standard (Entry Mod Note: Depending or MHz.	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) f n the memory configura	RDIMM RDIMM tion and processor model	, the memory speed mo	ıy run at 1333 MHz, 1	066 MHz or 800
Maximum memory	Standard (Base Mod Standard (Entry Mod Note: Depending or MHz. Please see the Onlir 192 GB RDIMM	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) f n the memory configura	RDIMM RDIMM tion and processor model	the memory speed mo	y run at 1333 MHz, 1	066 MHz or 800
,	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) f n the memory configura	RDIMM RDIMM tion and processor model	, the memory speed mo	ıy run at 1333 MHz, 1	066 MHz or 800
Memory slots	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) f n the memory configuration ne Memory Configuration	RDIMM RDIMM tion and processor model on Tool.	, the memory speed mo	ıy run at 1333 MHz, 1	066 MHz or 800
Maximum memory Memory slots Advanced memory protection Storage type	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS,	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) to the memory configuration me Memory Configuration rored memory, lock-step /SATA	RDIMM RDIMM tion and processor model on Tool.	, the memory speed mo	ıy run at 1333 MHz, 1	066 MHz or 800
Advanced memory protection Storage type	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS,	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) to the memory configuration me Memory Configuration rored memory, lock-step /SATA	RDIMM RDIMM tion and processor model on Tool.	, the memory speed mo	iy run at 1333 MHz, 1	066 MHz or 800
Advanced memory protection Storage type Maximum number of hard drives	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS,	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Memory Configuration of the Memory Configuration of the Memory Configuration of the Memory, lock-step // SATA	RDIMM RDIMM tion and processor model on Tool. o mode		iy run at 1333 MHz, 1	066 MHz or 800
Advanced memory protection Storage type Maximum number of hard drives	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in	Jels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Memory Configuration of the Memory Configuration of the Memory, lock-step of the Memory Configuration of the Memory, lock-step of the Memory Configuration of the Memory of	RDIMM RDIMM tion and processor model on Tool. mode mode	or hard drives		066 MHz or 800
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in	Jels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Memory Configuration of the Memory Configuration of the Memory, lock-step of the Memory Configuration of the Memory, lock-step of the Memory Configuration of the Memory of	RDIMM RDIMM tion and processor model on Tool. o mode	or hard drives		066 MHz or 800
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots	Standard (Base Moc Standard (Entry Mor Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Mem	RDIMM RDIMM tion and processor model on Tool. mode mode	or hard drives e latest I/O performanc	e	
Aemory slots Advanced memory protection Itorage type Aaximum number of hard drives Aaximum number of hard drives noted expansion slots Itorage controller	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Mem	RDIMM RDIMM tion and processor model on Tool. mode mode 14) 3.5-in Large Form Fact ots to provide you with the	or hard drives e latest I/O performanc	e	
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Mem	RDIMM RDIMM tion and processor model on Tool. mode mode 14) 3.5-in Large Form Fact ots to provide you with the	or hard drives e latest I/O performanc	e	
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller Deployment	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41 and 1 GB FBWC op	dels) – 6 GB (3 x 2 GB) del) – 4 GB (2 x 2 GB) for the memory configuration of the Mem	RDIMM RDIMM tion and processor model on Tool. mode mode 14) 3.5-in Large Form Fact ots to provide you with the	or hard drives e latest I/O performanc	e	
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller Deployment Form factor Rack height	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41 and 1 GB FBWC op	dels) – 6 GB (3 x 2 GB) to the Memory Configuration the Memory Configuration to the Me	RDIMM RDIMM tion and processor model on Tool. o mode 14) 3.5-in Large Form Fact ots to provide you with the MB, 512 MB battery-back	or hard drives e latest I/O performanc	e	
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller Deployment Form factor Rack height Networking	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41 and 1 GB FBWC op Rack or tower 4U HP NC375i Quad P	dels) – 6 GB (3 x 2 GB) to the Memory Configuration the Memory Configuration to the Me	RDIMM	or hard drives e latest I/O performanc ed write cache (BBWC)	e	
Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller Deployment Form factor Rack height Networking Infrastructure management	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41 and 1 GB FBWC op Rack or tower 4U HP NC375i Quad P HP ProLiant Onboar HP Insight Control st	dels) – 6 GB (3 x 2 GB) to the Memory Configuration the Memory Configuration to the Me	RDIMM RDIMM RDIMM tion and processor model on Tool. o mode 14) 3.5-in Large Form Fact ots to provide you with the MB, 512 MB battery-back	or hard drives e latest I/O performanc ed write cache (BBWC)	e	
Memory slots Advanced memory protection Storage type Maximum number of hard drives Maximum number of hard drives noted Expansion slots Storage controller Deployment	Standard (Base Moc Standard (Entry Moc Note: Depending or MHz. Please see the Onlin 192 GB RDIMM 48 GB UDIMM 18 DIMMs Advanced ECC, mir Hot-plug 2.5-in SAS, Hot-plug 3.5-in SAS, 24 Supports (24) 2.5-in 9 available PCI Exp HP Smart Array P41 and 1 GB FBWC op Rack or tower 4U HP NC375i Quad P	dels) – 6 GB (3 x 2 GB) to the Memory Configuration the Memory Configuration to the Me	RDIMM	or hard drives e latest I/O performanc ed write cache (BBWC)	e	

Growing businesses with expandability requirements

Designed to meet the requirements of growing businesses, the DL370 G6 and the ML370 G6 servers have nine available I/O slots that support PCI Express Gen2. And what about storage capacity, you may ask. Put your fears to rest, as the 8-bay standard drive cage provides up to 4.8 TB of storage (8 x 600 GB).

Critical remote sites

You need not worry about connectivity or performance when you are working in a remote location. The new HP ProLiant Onboard Administrator and HP Systems Insight Manager (SIM) make sure that you get enterprise-class management features, providing proven availability and uptime for critical applications.

Rendering and visualisation requirements

The HP ProLiant DL370 G6 and the HP ProLiant ML370 G6 Servers support 3 x 16 PCI Express slots, allowing support for up to three 300 W graphic cards, making these servers ideal solutions for rendering and visualisation requirements.

Options include

- Easy tower-to-rack conversion in the case of the ProLiant ML370 G6 Servers, which includes a tower-to-rack conversion kit
- USB 2.0 support five total USBs (two front; two rear; and, for security purposes, one internal)
- Up to 24 Small Form Factor drives and up to 14 Large Form Factor drives
- Hot-plug fans and power with optional redundancy
- HP Graphic Card Adapter Kit enabling support for up to three 300 W graphic cards

For more information about the HP ProLiant DL370 G6 and the HP ProLiant ML370 G6 Servers, visit: www.hp.com/servers/dl370-g6 or www.hp.com/servers/ml370-g6

HP Services

When technology works, business works

The challenge of virtually every IT organisation is similar: to develop and maintain an agile, efficient server infrastructure that delivers the service levels your business needs. HP Technology Services offers a comprehensive portfolio of HP Care Pack Services to help design, deploy, manage and support your IT environment.

Minimum recommended HP Care Pack offerings

- 3-year, same business day, 4-hour response onsite; 24x7 coverage, hardware support
- Integrated hardware plus operating system installation and start up

Enhanced service level Care Pack offerings

- 3-year Support Plus 24: Integrated 24x7 hardware and software operating support
- **Proactive Select:** Access to HP technical consultants, purchase service credits and obtain expertise when needed

Benefit from HP Care Pack Services, helping you:

- Reduce deployment time and manage ProLiant server solutions smoothly and efficiently
- Increase uptime and performance of server availability to your business
- Detect, diagnose and repair problems quickly to save time, money and resources

For more information, visit:

www.hp.com/services/proliantservices or www.hp.com/go/proliant/carepack

- High-performance models with a second processor, SAS controller, extra memory, redundant fans and power supplies
- HP Insight Control suite helps you deploy servers rapidly, proactively monitor system health and performance, improve power consumption and take total remote control of your infrastructure

HP Financial Services

HP Financial Services provides innovative financing and financial asset management programs to help you cost-effectively acquire, manage and ultimately retire your HP solutions. For more information on these services, visit:

www.hp.com/go/hpfinancialservices

Share with colleagues





